NSN 5305-01-135-9495

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-135-9495



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.294 inches and 0.375 inches Fastener Length: Between 0.344 inches and 0.375 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches Locking Feature: Patch threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.094 inches and 0.095 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c **Minimum Yield Strength:** 155000 pounds per square inch Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 6 type Shelf Life: N/a

NSN 5305-01-135-9495

Socket Head Cap Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

