NSN 5305-01-135-9501

Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-135-9501



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.444 inches and 0.494 inches Fastener Length: Between 0.892 inches and 0.922 inches **Head Style:** Pan **Head Diameter:** Between 0.568 inches and 0.593 inches **Head Height:** Between 0.162 inches and 0.183 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches Grip Length: Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches threads **Product Name:** Navy special project Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:**

80205-nas1985 professional/industrial association standard

NSN 5305-01-135-9501

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

