Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-136-6119



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 1.210 inches and 1.500 inches Fastener Length: Between 1.710 inches and 1.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches Hole Diameter: Between 0.044 inches and 0.050 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.188 inches and 0.190 inches **Hole Quantity:** 6 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b **Minimum Yield Strength:** 30000 pounds per square inch Hole Configuration Style: Round internal hexagon Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp xm-7 or steel comp 384 Surface Treatment: Passivate **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

NSN 5305-01-136-6119

Socket Head Cap Screw - Page 2 of 2

Thread Series Designator:

Unc

Specification Or Standard:

6 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

