NSN 5305-01-136-7149



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-136-7149 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.444 inches and 0.494 inches **Fastener Length:** Between 0.954 inches and 0.984 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.574 inches and 0.637 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel comp e4340 or steel comp 8740 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 3rd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

Demilitarization: No

Unit Of Measure:

N/a

NSN 5305-01-136-7149

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.