## NSN 5305-01-136-7437

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-136-7437 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.634 inches and 0.766 inches **Fastener Length:** Between 0.734 inches and 0.766 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **Locking Feature:** Strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.188 inches and 0.190 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 306 fastener or steel comp 316 fasten steel comp xm-7 fastener **Material Specification:** Astm a493 assn standard all material responses fastener **Surface Treatment:** Passivate fastener **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response fastener

Shelf Life: N/a

Unrc

**Thread Series Designator:** 

## NSN 5305-01-136-7437

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0