

View Online at <https://aerobasegroup.com/nsn/5305-01-137-3938>

**Fastener Length:**

Between 0.720 inches and 0.750 inches

**Head Height:**

Between 0.202 inches and 0.240 inches

**Width Between Flats:**

Between 0.367 inches and 0.375 inches

**Extended Washer Diameter:**

Between 0.480 inches and 0.520 inches

**Extended Washer Thickness:**

Between 0.030 inches and 0.050 inches

**Internal Drive Style:**

W/o internal drive

**Features Provided:**

Casehardened

**Min. Tensile Strength (psi):**

150000 pounds per square inch

**Hardness Rating:**

32.0 rockwell c and 38.0 rockwell c

**Nonmachine Thread Style:**

Blunt (type tt)

**Nonmachine Thread Diameter:**

0.250 inches

**Material:**

Steel comp 4037

**Material Specification:**

66 federal standard single material response

**Surface Treatment:**

Cadmium or chromate

**Surface Treatment Specification:**

Qq-p-416 ty2 cl2 federal specification 1st treatment response or mil-c-81562 ty2 cl2 military specification 2nd treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-81562 spec.