

View Online at <https://aerobasegroup.com/nsn/5305-01-137-5217>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.074 inches and 0.181 inches

**Fastener Length:**

Between 0.219 inches and 0.250 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.257 inches and 0.279 inches

**Locking Feature:**

Patch threads or pellet threads or strip threads

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Countersink Angle:**

Between 80.0 degrees and 82.0 degrees

**Material:**

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924 class 3 military specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.