

View Online at <https://aerobasegroup.com/nsn/5305-01-137-7042>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.477 inches and 0.637 inches

**Fastener Length:**

Between 0.767 inches and 0.787 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.360 inches and 0.404 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.250 inches

**Width Across Flats:**

Between 0.1562 inches and 0.1587 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches grip

**Special Features:**

Three slots 0.040 in. Wide by 0.029 in. Deep along the longitudinal axis and 120 degrees apart, thread to be double lead

**Material:**

Steel comp 8740 or steel comp 4140

**Material Specification:**

Mil-s-6049 military specification 1st material response or mil-s-5626 military specification 2nd material response

**Surface Treatment:**

Tin

**Surface Treatment Specification:**

Mil-t-10727 ty1 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6049 spec.