## NSN 5305-01-137-7043

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-137-7043

Thread Class:

3a

Ju

**Thread Direction:** 

Right-hand

Thread Length:

1.000 inches

**Fastener Length:** 

Between 2.940 inches and 3.000 inches

**Head Style:** 

Flat chamfer

**Head Diameter:** 

Between 0.365 inches and 0.375 inches

**Head Height:** 

Between 0.244 inches and 0.250 inches

**Internal Drive Style:** 

Hexagon

**Thread Diameter:** 

0.250 inches

Width Across Flats:

Between 0.188 inches and 0.190 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

**Minimum Yield Strength:** 

30000 pounds per square inch

Material:

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp xm-7 or steel comp 384

**Material Specification:** 

66 federal standard all material responses or astm a493 assn standard all material responses

**Surface Treatment:** 

**Passivate** 

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unrc

**Specification Data:** 

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

## NSN 5305-01-137-7043

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0