NSN 5305-01-137-9710

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-137-9710 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.218 inches and 0.310 inches **Fastener Length:** Between 0.280 inches and 0.310 inches **Head Style:** Hexagon **Head Height:** Between 0.080 inches and 0.093 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Internal Drive Style:** Tri-wing recess **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Steel comp e4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 class 2 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas5901 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig: A500d0

No

NSN 5305-01-137-9710

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.