NSN 5305-01-138-2689

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-138-2689

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| |
| Right-hand |
| Thread Length: |
| Between 1.700 inches and 1.811 inches |
| Fastener Length: |
| Between 1.796 inches and 1.843 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.105 inches and 0.120 inches |
| Width Between Flats: |
| Between 0.305 inches and 0.314 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.190 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Screw Material: |
| Iron alloy 660 |
| Screw Material Specification: |
| Ams 5731 assn standard single material response or ams 5737 assn standard single material response |
| Screw Surface Treatment: |
| Passivate |
| Screw Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unif |
| |
| Specification Data: |
| 80205-nas1802 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A500d0 |