## NSN 5305-01-138-4695

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-138-4695 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.380 inches **Fastener Length:** 1.060 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.440 inches **Head Height:** 0.250 inches First Diameter From Head: 0.146 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.680 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 202 or steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 403 or steel comp 405 or steel comp 410 or steel comp 414 or steel comp 420 or steel comp 430 or steel comp 440a or steel comp 440b or steel comp 440c or steel comp 446 **Material Specification:** Qq-s-763, cond a federal specification single material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-f-13924 cl 3 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

**Unit Of Measure:** 

Demilitarization:

## NSN 5305-01-138-4695

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-13924 spec.