
3a

Socket Head Cap Screw - Page 1 of 2





## **Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.262 inches and 0.375 inches Fastener Length: Between 0.345 inches and 0.375 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.300 inches and 0.310 inches **Head Height:** Between 0.100 inches and 0.190 inches Hole Diameter: 0.050 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.100 inches and 0.150 inches Hole Quantity: Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b **Minimum Yield Strength:** 30000 pounds per square inch Hole Configuration Style: Round internal hexagon Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 **Material Specification:** 66 federal standard all material responses **Thread Series Designator:**

Unjc

1

## NSN 5305-01-138-4702

Socket Head Cap Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

