NSN 5305-01-138-5486

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-138-5486 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** 3.965 inches **Head Style:** Flat chamfer **Head Diameter:** 0.312 inches **Head Height:** 0.200 inches **First Diameter From Head:** 0.272 inches **Second Diameter From Head:** Between 0.210 inches and 0.213 inches **Third Diameter From Head:** 0.272 inches **Fourth Diameter From Head:** Between 0.117 inches and 0.127 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.560 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.589 inches and 0.592 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 3.080 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 3.465 inches **Internal Drive Style: Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 4 Material:

Steel comp 303

Material Specification:

Astm a582 assn standard single material response

NSN 5305-01-138-5486

Externally Relieved Body Screw - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0