## NSN 5305-01-138-6290

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-138-6290 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.070 inches and 0.148 inches **Fastener Length:** Between 0.157 inches and 0.188 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.150 inches and 0.172 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 55000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Copper alloy **Screw Material Specification:** Qq-b-613 federal specification single material response or qq-b-626 federal specification single material response or qq-w-321 federal specification single material response **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924, cl 4 military specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 3 type and 2c style Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig:

No

A500d0

## NSN 5305-01-138-6290

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.