NSN 5305-01-138-7226

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-138-7226 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.710 inches and 0.812 inches **Fastener Length:** Between 0.781 inches and 0.812 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.367 inches and 0.375 inches **Head Height:** Between 0.133 inches and 0.150 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2 class 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1101 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A500d0