NSN 5305-01-139-0383

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-139-0383 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.115 inches and 0.125 inches **Fastener Length:** 0.430 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.067 inches and 0.072 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.305 inches and 0.315 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project **Special Features:** Color black Material: Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 **Material Specification:** Qq-s-763 federal specification all material responses **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, class 4 military specification single treatment response **Thread Series Designator:**

N/a

Unc

Shelf Life:

NSN 5305-01-139-0383

Externally Relieved Body Screw - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.