## NSN 5305-01-139-0849

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-139-0849

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.378 inches and 0.428 inches  |
| Fastener Length:   |
| Between 1.888 inches and 1.918 inches  |
| Head Style:  |
| Flat countersunk   |
| Head Diameter:   |
| Between 0.464 inches and 0.507 inches  |
| Grip Diameter:   |
| Between 0.2485 inches and 0.2495 inches  |
| Internal Drive Style:  |
| High-torque  |
| Thread Diameter:   |
| 0.250 inches   |
| Grip Length:   |
| Between 1.490 inches and 1.510 inches  |
| Thready Qty Per Inch (tpi):  |
| 28   |
| Min. Tensile Strength (psi):   |
| 160000 pounds per square inch  |
| Countersink Angle:   |
| Between 99.0 degrees and 101.0 degrees   |
| Surface Finish:  |
| 32.0 microinches threads   |
| Material:  |
| Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 |
| Surface Treatment:   |
| Cadmium and chromate   |
| Surface Treatment Specification:   |
| Qq-p-416, type 2, cl 2 federal specification single treatment response                       |
| Thread Series Designator:  |
| Unjf   |
| Specification Data:  |
| 80205-nas1580 professional/industrial association standard                                   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |

## NSN 5305-01-139-0849

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

