## NSN 5305-01-139-2055

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-139-2055

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.476 inches and 0.526 inches
Fastener Length:
Between 1.736 inches and 1.766 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.578 inches and 0.633 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.312 inches
Grip Length:
Between 1.240 inches and 1.260 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1580 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-01-139-2055

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0