NSN 5305-01-140-2481

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-140-2481 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.156 inches **Fastener Length:** Between 0.490 inches and 0.510 inches **Head Style:** Fillister **Head Diameter:** Between 0.166 inches and 0.182 inches **Head Height:** Between 0.070 inches and 0.078 inches **First Diameter From Head:** Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.303 inches and 0.323 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Color black Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 class 3 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-140-2481

Externally Relieved Body Screw - Page 2 of 2



_										
וו	0	m	ш	м	•	iza	31	^	n	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.