Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-140-3051

| Thread Class:  |  |
|--|--|
| 2a   |  |
| Thread Direction:  |  |
| Right-hand   |  |
| Thread Length:   |  |
| 0.200 inches   |  |
| Fastener Length:   |  |
| 0.600 inches   |  |
| Head Style:  |  |
| Pan  |  |
| Head Diameter:   |  |
| Between 0.205 inches and 0.219 inches  |  |
| Head Height:   |  |
| Between 0.070 inches and 0.080 inches  |  |
| First Diameter From Head:  |  |
| 0.080 inches   |  |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter:                      |  |
| 0.400 inches   |  |
| Internal Drive Style:  |  |
| Cross recess type 1  |  |
| Thread Diameter:   |  |
| 0.112 inches   |  |
| Thready Qty Per Inch (tpi):  |  |
| 40   |  |
| Externally Relieved Body Diameter Quantity:  |  |
| 1  |  |
| Product Name:  |  |
| Navy special project   |  |
| Material:  |  |
| Steel comp 302 or steel comp 303   |  |
| Material Specification:  |  |
| Qq-s-763 federal specification single material response or 66 federal standard single mater  | rial response                            |
| Surface Treatment:   |  |
| Passivate and oxide  |  |
| Surface Treatment Specification:   |  |
| Qq-p-35, type 2 federal specification 1st treatment response and mil-c-13924, class 4 milita | ary specification 2nd treatment response |
| Thread Series Designator:  |  |
| Unc  |  |
| Shelf Life:  |  |
| N/a  |  |
| Unit Of Measure:   |  |
|  |  |



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.