

View Online at <https://aerobasegroup.com/nsn/5305-01-140-4547>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.502 inches and 0.532 inches

Fastener Length:

Between 4.090 inches and 4.130 inches

Head Diameter:

Between 0.729 inches and 0.750 inches

Head Height:

Between 0.302 inches and 0.312 inches

First Diameter From Head:

0.477 inches

Second Diameter From Head:

0.496 inches

Third Diameter From Head:

0.291 inches

Fourth Diameter From Head:

0.375 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.093 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

3.495 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

3.588 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

4.090 inches

Thread Diameter:

0.375 inches

Width Across Flats:

0.250 inches

Thready Qty Per Inch (tpi):

16

Hardness Rating:

32.0 rockwell c and 43.0 rockwell c

Externally Relieved Body Diameter Quantity:

4

Material:

Steel

Material Specification:

Mil-s-21472 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-21472 spec.