

View Online at <https://aerobasegroup.com/nsn/5305-01-140-4794>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.287 inches and 0.337 inches

**Fastener Length:**

Between 0.797 inches and 0.827 inches

**Head Style:**

Oval countersunk

**Head Diameter:**

Between 0.390 inches and 0.395 inches

**Grip Diameter:**

Between 0.2490 inches and 0.2495 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.081 inches first hole

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.490 inches and 0.510 inches

**Thready Qty Per Inch (tpi):**

28

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.676 inches first hole and 0.716 inches first hole

**Material:**

Stainless steel

**Material Specification:**

23-112 fscm 76301 mfr ref single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0