## NSN 5305-01-140-5711

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-140-5711 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.095 inches and 0.188 inches **Fastener Length:** Between 0.157 inches and 0.188 inches **Head Style:** Watertight **Head Diameter:** Between 0.335 inches and 0.347 inches **Head Height:** Between 0.109 inches and 0.115 inches **Locking Feature:** Strip threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 75000 pounds per square inch **Special Features:** Furnished with rubber o-ring Material: Steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 **Material Specification:** Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or qq-s-763 federal specification 3rd material response or astm a493 assn standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5305-01-140-5711

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0