

View Online at <https://aerobasegroup.com/nsn/5305-01-140-5711>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.095 inches and 0.188 inches

**Fastener Length:**

Between 0.157 inches and 0.188 inches

**Head Style:**

Watertight

**Head Diameter:**

Between 0.335 inches and 0.347 inches

**Head Height:**

Between 0.109 inches and 0.115 inches

**Locking Feature:**

Strip threads

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

75000 pounds per square inch

**Special Features:**

Furnished with rubber o-ring

**Material:**

Steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7

**Material Specification:**

Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or qq-s-763 federal specification 3rd material response or astm a493 assn standard all material responses

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0