NSN 5305-01-140-6362

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-140-6362

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.378 inches and 0.428 inches
Fastener Length:
Between 0.575 inches and 0.605 inches
Head Style: Flat countersunk
Head Diameter:
Between 0.464 inches and 0.506 inches
Grip Diameter:
Between 0.2485 inches and 0.2490 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Grip Length:
Between 0.177 inches and 0.197 inches
Thready Qty Per Inch (tpi):
28 Hardness Bating
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees Surface Finish:
32.0 microinches threads Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 class 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1580 professional/industrial association standard
Shelf Life:
Unit Of Measure:

NSN 5305-01-140-6362

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

