3a

1

Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-140-7963



## **Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.598 inches and 0.690 inches Fastener Length: Between 0.660 inches and 0.690 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.085 inches and 0.096 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 44.0 rockwell c and 48.0 rockwell c **Primary Washer Outside Diameter:** Between 0.370 inches and 0.380 inches **Primary Washer Style:** Flat **Primary Washer Material Thickness:** Between 0.017 inches and 0.023 inches Material: Steel fastener **Material Specification:** Sae assn standard single material response primary washer Surface Treatment: Zinc and dichromate **Surface Treatment Specification:** Gm 4342-m code z0d48 fscm 16764 mfr ref single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

## NSN 5305-01-140-7963

Assembled Washer Screw - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0