NSN 5305-01-141-6641

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-141-6641
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.500 inches
Fastener Length:
0.500 inches
Head Style:
Pan no. 2
Head Diameter:
0.219 inches
Head Height:
0.218 inches
Washer Quantity:
2
Internal Drive Style:
Slot
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
55000 pounds per square inch
Secondary Washer Relationship To Primary Washer:
Not identical
Secondary Washer Style:
Flat
Primary Washer Outside Diameter:
0.209 inches
Secondary Washer Outside Diameter:
0.213 inches
Primary Washer Style:
Split helical ring
Primary Washer Material Thickness:
0.025 inches
Secondary Washer Material Thickness:
0.016 inches
Material:
Copper alloy 510 primary washer
Surface Treatment

Tin

NSN 5305-01-141-6641

Assembled Washer Screw - Page 2 of 2



Thread Series Designator:
Unc
Specification Data:
80205-nas 720 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0