NSN 5305-01-141-7900

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-141-7900

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.615 inches and 0.682 inches |
| Fastener Length: |
| Between 1.687 inches and 1.734 inches |
| Head Style: |
| Flat countersunk undercut |
| Head Diameter: |
| Between 0.756 inches and 0.760 inches |
| Head Height: |
| Between 0.1017 inches and 0.1037 inches |
| Shoulder Diameter: |
| 0.4052 inches first shoulder and 0.4057 inches first shoulder |
| Shoulder Length: |
| 0.948 inches first shoulder and 0.970 inches first shoulder |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.375 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Countersink Angle: |
| 100.0 degrees |
| Shoulder Shape: |
| Round first shoulder |
| Special Features: |
| Furnished with one rubber o ring |
| Material: |
| Steel comp xm-13 |
| Material Specification: |
| Ams5629 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5305-01-141-7900

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0