NSN 5305-01-142-2901

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-142-2901 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.295 inches and 0.375 inches **Fastener Length:** Between 0.345 inches and 0.375 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Steel comp 4140 or steel comp e4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Screw Surface Treatment Specification:** Qq-p-416 type 2 class 3 federal specification single treatment response **Special Features:** Furnished with boot type nylon washer 0.312 in. O.D, head and washer color gray per federal standard 595 no 26307 **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Mil-std (military Standard): Mil-s-5626 spec.

Fiig: A500d0