NSN 5305-01-142-4874

Shoulder Screw - Page 1 of 1





View Online at https://aerobasegroup.com/nsn/5305-01-142-4874

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.305 inches and 0.362 inches |
| Fastener Length: |
| Between 1.565 inches and 1.612 inches |
| Head Style: |
| Oval countersunk |
| Head Diameter: |
| Between 0.297 inches and 0.302 inches |
| Shoulder Diameter: |
| 0.2021 inches first shoulder and 0.2026 inches first shoulder |
| Shoulder Length: |
| 1.205 inches first shoulder and 1.224 inches first shoulder |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.190 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Shoulder Shape: |
| Round first shoulder |
| Material: |
| Steel comp xm-13 |
| Material Specification: |
| Ams5629 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| |
| |