## NSN 5305-01-142-6290

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-142-6290 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.380 inches and 0.447 inches **Fastener Length:** Between 0.828 inches and 0.875 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.377 inches and 0.381 inches **Head Height:** Between 0.039 inches and 0.041 inches **Shoulder Diameter:** 0.2021 inches first shoulder and 0.2026 inches first shoulder **Shoulder Length:** 0.387 inches first shoulder and 0.409 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Furnished with one rubber o ring Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## **NSN 5305-01-142-6290** Shoulder Screw - Page 2 of 2



Fiig:

A003b0