

View Online at <https://aerobasegroup.com/nsn/5305-01-142-7197>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.291 inches and 0.341 inches

Fastener Length:

Between 2.051 inches and 2.081 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.497 inches and 0.507 inches

Shoulder Diameter:

0.2802 inches first shoulder and 0.2807 inches first shoulder

Shoulder Length:

1.645 inches first shoulder and 1.665 inches first shoulder

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.081 inches first hole

Internal Drive Style:

High-torque

Thread Diameter:

0.250 inches

Thread Qty Per Inch (tpi):

28

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.928 inches first hole and 1.968 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0