## NSN 5305-01-142-8395



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-142-8395 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.291 inches and 0.341 inches **Fastener Length:** Between 2.051 inches and 2.081 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.497 inches and 0.507 inches **Shoulder Diameter:** 0.2646 inches first shoulder and 0.2651 inches first shoulder **Shoulder Length:** 1.641 inches first shoulder and 1.661 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.081 inches first hole **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 1.928 inches first hole and 1.968 inches first hole **Shoulder Shape:** Round first shoulder Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Oriji

Shelf Life:

N/a

## NSN 5305-01-142-8395

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0