

View Online at <https://aerobasegroup.com/nsn/5305-01-142-8399>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.630 inches and 0.697 inches

**Fastener Length:**

Between 1.828 inches and 1.875 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

Between 0.881 inches and 0.888 inches

**Head Height:**

Between 0.113 inches and 0.120 inches

**Shoulder Diameter:**

0.4677 inches first shoulder and 0.4682 inches first shoulder

**Shoulder Length:**

1.058 inches first shoulder and 1.085 inches first shoulder

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.438 inches

**Thready Qty Per Inch (tpi):**

20

**Countersink Angle:**

100.0 degrees

**Shoulder Shape:**

Round first shoulder

**Special Features:**

Furnished with one rubber o ring

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0