## NSN 5305-01-142-8399

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-142-8399 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.630 inches and 0.697 inches **Fastener Length:** Between 1.828 inches and 1.875 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.881 inches and 0.888 inches **Head Height:** Between 0.113 inches and 0.120 inches **Shoulder Diameter:** 0.4677 inches first shoulder and 0.4682 inches first shoulder **Shoulder Length:** 1.058 inches first shoulder and 1.085 inches first shoulder **Internal Drive Style:** High-torque Thread Diameter: 0.438 inches Thready Qty Per Inch (tpi): 20 **Countersink Angle:** 100.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Furnished with one rubber o ring Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unjf

N/a **Unit Of Measure:** 

Shelf Life:

## NSN 5305-01-142-8399

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0