NSN 5305-01-142-9410

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-142-9410 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.225 inches and 0.275 inches **Fastener Length:** Between 0.360 inches and 0.390 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.328 inches and 0.333 inches **Shoulder Diameter:** 0.2177 inches first shoulder and 0.2182 inches first shoulder **Shoulder Length:** 0.065 inches first shoulder and 0.093 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: **Unit Of Measure:**

N/a
Unit Of Measure:
-Demilitarization:

NSN 5305-01-142-9410 Shoulder Screw - Page 2 of 2



Fiig:

A003b0