## NSN 5305-01-142-9413

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-142-9413 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.537 inches and 0.587 inches **Fastener Length:** Between 0.859 inches and 0.889 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.612 inches and 0.672 inches **Shoulder Diameter:** 0.4521 inches first shoulder and 0.4526 inches first shoulder **Shoulder Length:** 0.197 inches first shoulder and 0.237 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.438 inches Thready Qty Per Inch (tpi): 20 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## **NSN 5305-01-142-9413** Shoulder Screw - Page 2 of 2



Fiig:

A003b0