

View Online at <https://aerobasegroup.com/nsn/5305-01-142-9423>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.442 inches and 0.509 inches

**Fastener Length:**

Between 0.952 inches and 0.999 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

Between 0.502 inches and 0.507 inches

**Head Height:**

Between 0.058 inches and 0.060 inches

**Shoulder Diameter:**

0.2802 inches first shoulder and 0.2807 inches first shoulder

**Shoulder Length:**

0.430 inches first shoulder and 0.452 inches first shoulder

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Countersink Angle:**

100.0 degrees

**Shoulder Shape:**

Round first shoulder

**Special Features:**

Furnished with one rubber o ring

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0