NSN 5305-01-142-9909

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-142-9909 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.375 inches **Fastener Length:** Between 0.468 inches and 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 35.0 rockwell c primary washer and 43.0 rockwell c primary washer **Secondary Washer Relationship To Primary Washer:** Not identical **Secondary Washer Style: Primary Washer Outside Diameter:** 0.250 inches **Secondary Washer Outside Diameter:** Between 0.253 inches and 0.263 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.031 inches **Secondary Washer Material Thickness:** Between 0.013 inches and 0.019 inches Material: Steel comp 303se fastener or steel comp 302 fastener or steel comp 303 fastener or steel comp 430 fastener

Surface Treatment:

Passivate secondary washer

NSN 5305-01-142-9909

Assembled Washer Screw - Page 2 of 2



Surface Treatment Speci

Qq-p-35 federal specification single treatment response secondary washer

Thread Series Designator:

Unc

Specification Data:

80205-nas1301 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A003b0