## NSN 5305-01-143-2826

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-143-2826 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.287 inches and 0.337 inches **Fastener Length:** Between 0.735 inches and 0.765 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.297 inches and 0.301 inches **Shoulder Diameter:** 0.2021 inches first shoulder and 0.2026 inches first shoulder **Shoulder Length:** 0.383 inches first shoulder and 0.411 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 20 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5305-01-143-2826

Shoulder Screw - Page 2 of 2



Fiig:

A003b0