NSN 5305-01-143-2834

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-143-2834 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.442 inches and 0.509 inches **Fastener Length:** Between 1.390 inches and 1.437 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.502 inches and 0.507 inches **Head Height:** Between 0.058 inches and 0.060 inches **Shoulder Diameter:** 0.2802 inches first shoulder and 0.2807 inches first shoulder **Shoulder Length:** 0.868 inches first shoulder and 0.890 inches first shoulder **Internal Drive Style:** High-torque Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** 100.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Furnished with one rubber o ring Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unjf

Shelf Life: N/a **Unit Of Measure:**

NSN 5305-01-143-2834

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0