

View Online at <https://aerobasegroup.com/nsn/5305-01-143-4072>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.442 inches and 0.492 inches

**Fastener Length:**

Between 0.702 inches and 0.732 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.625 inches and 0.635 inches

**Shoulder Diameter:**

0.3427 inches first shoulder and 0.3432 inches first shoulder

**Shoulder Length:**

0.120 inches first shoulder and 0.140 inches first shoulder

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

24

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Shoulder Shape:**

Round first shoulder

**Special Features:**

Internal hexagon socket in threaded end 0.1270 in. Min and 0.1295 in. Maximum width across flats

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0