NSN 5305-01-143-4082

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-143-4082 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.630 inches and 0.697 inches **Fastener Length:** Between 1.515 inches and 1.562 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.881 inches and 0.888 inches **Head Height:** Between 0.124 inches and 0.127 inches **Shoulder Diameter:** 0.4521 inches first shoulder and 0.4526 inches first shoulder **Shoulder Length:** 0.738 inches first shoulder and 0.761 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.438 inches Thready Qty Per Inch (tpi): 20 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Furnished with one rubber o ring Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-143-4082 Shoulder Screw - Page 2 of 2



Fiig:

A003b0