NSN 5305-01-143-5040

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-143-5040 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.506 inches and 0.573 inches **Fastener Length:** Between 1.828 inches and 1.875 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.629 inches and 0.634 inches **Head Height:** Between 0.082 inches and 0.084 inches **Shoulder Diameter:** 0.3271 inches first shoulder and 0.3276 inches first shoulder **Shoulder Length:** 1.218 inches first shoulder and 1.240 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Furnished with one rubber o ring Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-143-5040 Shoulder Screw - Page 2 of 2



Fiig:

A003b0