NSN 5305-01-143-6506

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-143-6506 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.345 inches and 0.420 inches **Fastener Length:** Between 1.110 inches and 1.155 inches **Head Style:** Pan **Head Diameter:** Between 0.282 inches and 0.294 inches **Head Height:** Between 0.092 inches and 0.097 inches **First Diameter From Head:** Between 0.097 inches and 0.102 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.735 inches and 0.765 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Furnished with o-ring, bearing surface of head grooved for o-ring Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 384 **Material Specification:** Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or qq-s-763 federal specification 3rd material response or astm a493 assn standard 4th material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

--

N/a

Unit Of Measure:

NSN 5305-01-143-6506

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0