Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-143-6520



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.345 inches and 0.438 inches Fastener Length: Between 0.407 inches and 0.438 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches Locking Feature: Strip threads or patch threads or pellet threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Steel comp 4140 or steel comp e4340 or steel comp 8740 Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 class 2 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1190 professional/industrial association standard Shelf Life: N/a Unit Of Measure:

NSN 5305-01-143-6520

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

