NSN 5305-01-143-6533

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-143-6533

Thread Class:
3a
Thread Direction:
Right-hand Thread Longth:
Thread Length: Between 0.170 inches and 0.250 inches
Fastener Length: Between 0.220 inches and 0.250 inches
Head Style: Flat chamfer
Head Diameter:
Between 0.176 inches and 0.183 inches
Head Height:
Between 0.108 inches and 0.112 inches
Hole Diameter:
Between 0.033 inches and 0.039 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.112 inches
Width Across Flats:
0.095 inches
Hole Quantity:
2
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Material:
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7
Surface Treatment:
Cadmium
Surface Treatment Specification.

Surface Treatment Specification:

Qq-p-416 type 1 class 2 federal specification single treatment response

NSN 5305-01-143-6533

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:
Unrc
Specification Data:
80205-nas1352 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia·

A003b0