NSN 5305-01-143-6537

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-143-6537

View Online at https://aerobasegroup.com/nsn/5305-01-143-6537
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.378 inches and 0.428 inches
Fastener Length:
Between 0.700 inches and 0.730 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.464 inches and 0.507 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.250 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single
material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1580 professional/industrial association standard

N/a

Shelf Life:

NSN 5305-01-143-6537

Close Tolerance Screw - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0