## NSN 5305-01-143-8631

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-143-8631

| Thread Direction:  |
|--|
| Right-hand   |
| Thread Length:   |
| 6.0 millimeters  |
| Fastener Length:   |
| 6.0 millimeters  |
| Head Style:  |
| Flat countersunk   |
| Head Diameter:   |
| Between 4.5 millimeters and 5.0 millimeters  |
| Internal Drive Style:  |
| Torque set   |
| Thread Diameter:   |
| 2.5 millimeters  |
| Min. Tensile Strength (psi):   |
| 1100 megapascals   |
| Thread Pitch In Millimeters:   |
| 0.4  |
| Countersink Angle:   |
| Between 99.5 degrees and 100.5 degrees   |
| Product Name:  |
| Screw, machine, 100deg flush head, offset cruciform recess, full thread, a286 cres, 1100 mpa, metric |
| Screw Material:  |
| Iron alloy 660   |
| Screw Material Specification:  |
| Na0026 national specification single material response   |
| Screw Surface Treatment:   |
| Passivate  |
| Screw Surface Treatment Specification:   |
| Qq-p-35 federal specification single treatment response  |
| Bearing Surface Of Head Surface Finish:  |
| 0.8 micrometers  |
| Shank Surface Finish:  |
| 0.8 micrometers  |
| Thread Surface Finish:   |
| 0.8 micrometers  |
| Thread Series Designator:  |
| Mj   |
| Specification Data:  |
| 80205-na0026 professional/industrial association specification                                       |
| Shelf Life:  |

N/a

## NSN 5305-01-143-8631

Machine Screw - Page 2 of 2



|  |  |  | ure: |  |
|--|--|--|------|--|
|  |  |  |      |  |
|  |  |  |      |  |

--

Demilitarization:

No

Fiig:

A500d0